

# Narrow Bezel 6.7



46" at 450 nit

## specifications

		ZV46B	ZV46C
Panel Type		LED-backlit LCD	CCFL-backlit LCD
Number of Pixels		1920 x 1080	1366 x 768
Brightness (typ)		700 nit	450 nit
Contrast Ratio		3500:1	3000:1
Aspect Ratio		16:9	16:9
Viewing Angle		178°/178°	178°/178°
Bezel (combined)		6.7mm	6.7mm
Inputs/ Outputs	DVI	1	1
	VGA	1	1
	RS232	1	1
	AV	1	1
	Comp	1	1
Operating Temp.		41°F ~ 104°F	41°F ~ 104°F
Humidity		20% ~ 80%	20% ~ 80%
Input Voltage		100V ~ 240V	100V ~ 240V
Power Consump.		190W	200W
Standby Power Consumption		< 1W	< 1W
Lamp Lifetime		≥ 50,000hrs	≥ 50,000hrs
Dimensions (W x H x D)	Net	47.9 x 27 x 5.7	40.4 x 22.9 x 4
	Packed	53.5 x 33 x 12	46 x 29 x 9.5
Weight	Net	75lbs	47lbs
	Packed	90lbs	57lbs

### NB6.7 Narrow Bezel - 6.7mm

46" 450nit	46" 700nit
---------------	---------------

■ The ZDS Narrow Bezel display is available in 46" at both 450 and 700 nit. Its bezel size is only 6.7mm bezel to bezel. Its native resolution is 1366x768. The SNB is the most recommended solution and generally suits most digital signage needs.

### The ZDS Display Difference

- High Quality Display  
Up to 46t" diagonal, 6.7mm bezel
- Number of Pixels  
1920 x 1080(WUXGA), 1080p
- Panel Technology  
LED BACKLIT LCD / S-PVA TFT
- Aspect Ratio  
16:9
- Low Energy Consumption  
240W
- Active Display area(mm)  
1209.6x680.4
- High Brightness  
700nit
- High Contrast Ratio  
10,000:1 Dynamic Contrast Ratio
- Wide Viewing Angle (H/W)  
178° / 178°
- Longer Life Time  
50,000 hrs (2x standard life)